

W15P SIP Wall Speaker 15W

The W15P SIP wall speaker is suited for both indoor & undercover outdoor applications. It can work standalone or integrate with IP Phone systems enabling users to make announcements from IP Phones. W15P supports 2 SIP accounts, one account can be used as a loud ringer /alerter in noisy environments to notify users of phones ringing.



- SIP Enabled with Opus, G722 HD sound
- Integrates with IP PBX systems
- Supports P2P Paging and RTP Multicast
- Built in D class stereo 15W amplifier
- Supports scheduling of prerecorded messages
- Can be used as loud ringer
- Programming by web login
- IP55 water proof rating
- PoE for easy installation
- 30W model also available

Specifications

Audio Decoding	OPUS 48 kHz, G722 16 kHz, PCMU /PCMA 8 kHz, MP3 44.1 kHz.
Network Protocols	TCP/IP, UDP, ARP, ICMP, IGMP, SIP, RTSP, NTP, DHCP, HTTP, RTP, RTCP, FTP, TFTP, ONVIF
Speaker Acoustics	SPL 101dB, Signal to noise ratio 91dB, Harmonic distortion 0.1@1kHz
Speaker Frequency	Response 80Hz~20kHz, Range 500-2kHz +/-10dB, 400-125kHz +/- 20dB .
Operating temperature	-30°C~60°C, Operating humidity 5%~85%.
Dimensions & Weight	ABS IP55 rated enclosure 296 x 196 x 157 mm, 2.4 Kg.
Network and Power	RJ45 socket with PoE IEEE802.3af compliant, DC24V power connector.