

H30P SIP Horn Speaker - 30W

The H30P SIP Horn speaker is ideal for outdoor applications. It can work as standalone or integrate with IP Phone Systems enabling users to make announcements from IP Phones. H30P supports 2 SIP accounts, one account can also be used as a loud ringer/ alerter in noisy environments to notify users of phones ringing.



- SIP Enabled with Opus, G722 HD sound
- Integrates with IP PBX systems
- Supports P2P Paging and RTP Multicast
- Built in D class stereo 30W amplifier
- Supports scheduling of prerecorded messages
- Can be used as loud ringer
- Programming by web login
- IP67 Water proof enclosure
- PoE for easy installation
- 15W option available

Specifications

Audio Decoding	OPUS 48 kHz, G722 16 kHz, PCMU / PCMA 8 kHz, MP3 44.1 kHz.
Network Protocols	TCP/IP, UDP, ARP, ICMP, IGMP, SIP, RTSP, NTP, DHCP, HTTP, RTP, RTCP, FTP, TFTP, ONVIF
Speaker Acoustics	SPL 120dB, Harmonic distortion 0.1@1kHz , Signal to noise ratio 91dB
Speaker Frequency	Response 350Hz~8KHz , Range 500-2kHz +/-10dB, 400-125kHz +/- 20dB
Operating temperature	-30°C~+60°C, Operating Humidity 5%~85%.
Dimensions & Weight	ABS IP67 rated enclosure 285 x 205 x 290 mm, 2 Kg.
Network and Power	RJ45 socket with IEEE802.3af compliant PoE .